

SSQ Domiz[®] First, blue-grey





“We specified SSQ Domiz[®] First, blue-grey roofing slate for both technical and aesthetic reasons: its strength and quality gives the performance needed and its cold, hard, colour provides a dramatic foil to the rich warmth of the western red cedar walls.”

Mark Webber, Architect, Nichols Brown Webber



Product profile

SSQ Domiz blue-grey slate is mined especially for SSQ at a quarry in the Orense region of North West Spain and provides high-performance roofing slates.

In addition to passing SSQ's own, rigorous quality control tests, SSQ Domiz® First, blue-grey roofing slate has been tested in accordance with EN 12326, carries the CE marking and is classified as 'A1, T1, S1'.*

* Test results are available on request.

Appearance

SSQ Domiz slate is cold, hard, blue-grey coloured slate similar to that found in Devon, Cornwall and Scotland. The colour is totally natural and will not fade, even in the strongest sunlight or harshest environments.

Guarantee

SSQ Domiz® First, blue-grey roofing slate is covered by a 75-year guarantee.

Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
500 x 250	5 – 6	2100
400 x 250	5 – 6	1680
400 x 200	5 – 6	1344

Minimum headlap for fixing slates with nails or hooks according to BS 5534:2003

Moderate exposure (< 56.5 l/m² per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
500 x 250	115	105	95	85	80	70	60	55	50
400 x 250	–	–	–	–	80	70	60	55	50
400 x 200	–	–	–	–	80	70	60	55	50

Severe exposure (≥ 56.5 l/m² per spell)*

Size (mm)	Rafter pitch							
	22.5°	25°	27.5°	30°	35°	40°	45°	80°
500 x 250	130	120	110	100	90	80	70	65
400 x 250	–	–	–	100	90	80	70	65
400 x 200	–	–	–	100	90	80	70	65

Coverage

Nail fixing method

Size (mm)	Lap (mm)											
	50	65	75	80	90	100	110	115	120	130	140	
Number of slates/m ²												
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0	21.6	22.2	
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6	–	–	
400 x 200	28.6	29.9	30.8	31.3	32.3	33.3	34.5	35.1	35.7	–	–	

(NB: No allowance has been made for wastage*)

Hook fixing method

Size (mm)	Lap (mm)									
	50	65	75	80	85	90	95	100	105	
Number of slates/m ²										
500 x 250	17.8	18.4	18.8	19.0	19.3	19.5	19.8	20.0	20.3	
400 x 250	22.9	23.9	24.6	25.0	25.4	25.8	26.2	26.7	27.1	
400 x 200	28.6	29.9	30.8	31.3	31.7	32.3	32.8	33.3	33.9	

Size (mm)	Lap (mm)							
	110	115	120	125	130	135	140	145
Number of slates/m ²								
500 x 250	20.5	20.8	21.0	21.3	21.6	21.9	22.2	22.5
400 x 250	27.6	28.1	28.6	29.1	–	–	–	–
400 x 200	34.5	35.1	35.7	36.4	–	–	–	–

(NB: No allowance has been made for wastage*)

* Please refer to the SSQ Natural Roofing Slate Design and Fixing Guide for full details (available on www.ssqgroup.com).



SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS

T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

SSQ Northern Irish Office: Forsyth House, Cromac Square, Belfast BT2 8LA

T: +44 (0) 79 1239 0505 F: +44 (0) 28 9021 8001

SSQ Spanish Office: C/ Academia Dequit No. 11º A, 32300 El Barco de Valdeorras, Orense, Spain

E: info@ssq.co.uk W: www.ssqgroup.com

© Registered trademark, SSQ Group

